

Coslight Polymer Li-ion Battery

Model	Nominal Capacity (mAh) Discharge current:0.2C	Voltage (V)	Dimension (mm)		
			Thickness Tolerance(+0/-0.5)	Width Tolerance(+0/-1.0)	Height Tolerance(+0/-1.0)
CA411037	125	3.7	4.1	10.5	37.5
CA421040	130	3.7	4.2	10.5	40.5
CA661119	75	3.7	6.6	11.5	19.5
CA381223	65	3.7	3.8	12.5	23.5
CA701327	150	3.7	7.6	13.5	27.5
CA351328	90	3.7	3.5	13.5	28.5
CA651329	150	3.7	6.5	13.5	29.5
CA551430	160	3.7	5.5	14.5	30.5
CA621518	110	3.7	6.2	15.5	18.5
CA401550	260	3.7	4.0	15.5	50.5
CA801730	300	3.7	8.0	17.5	30.5
CA631823	210	3.7	6.3	18.5	23.5
CA481922	140	3.7	4.8	19.5	22.5
CA461946	400	3.7	4.6	19.5	46.5
CA402025	150	3.7	4.0	20.5	25.5
CA552025	150	3.7	5.5	20.5	25.5
CA482030	250	3.7	5.0	20.5	30.5
CA702030	350	3.7	7.0	20.5	30.5
CA602248	300	3.7	6.0	22.5	48.5
CA7823189	3600	3.7	7.8	23.5	189.5
CA522535	400	3.7	5.2	25.5	35.5
CA553045	650	3.7	5.5	30.5	45.5
CA503048	700	3.7	5.0	30.5	48.5
CA703048	1000	3.7	7.0	30.5	48.5
CA103048	1500	3.7	10	30.5	48.5
CA323450	550	3.7	3.2	34.5	50.5
CA383450	680	3.7	3.9	34.5	50.5
CA453450	800	3.7	4.5	34.5	50.5
CA553450	1060	3.7	5.5	34.5	50.5
CA383456	700	3.7	3.8	34.5	56.5
CA503456	1000	3.7	5.0	34.5	56.5
CA853465	1900	3.7	8.5	34.5	65.5
CA653495	2400	3.7	6.5	34.5	95.5
CA553553	1150	3.7	5.5	35.5	53.5
CA523635	620	3.7	5.2	36.5	35.5
CA623665	1750	3.7	6.2	36.5	65.5
CA803681	2550	3.7	8.0	36.5	81.5
CA883681	2900	3.7	8.8	36.5	81.5
CA603696	2150	3.7	5.8	36.5	96.5
CA583726	530	3.7	5.8	37.5	26.5
CA503759	1200	3.7	5.0	37.5	59.5
CA553759	1400	3.7	5.5	37.5	59.5
CA603759	1500	3.7	6.4	37.5	59.5
CA353762	1080	3.7	3.9	37.5	62.5
CA753783	2700	3.7	7.5	37.5	83.5
CA403946	930	3.7	4.3	39.5	46.5
CA503946	1030	3.7	5.0	39.5	46.5
CA393949	600	3.7	4.0	39.5	49.5
CA503965	1500	3.7	5.0	39.5	65.5
CA454061	1280	3.7	4.5	40.5	61.5

CA604071	2000	3.7	6.0	40.5	71.5
CA754090	2900	3.7	7.5	40.5	90.5
CA4240A1	1900	3.7	4.2	40.5	101.5
CA414161	1280	3.7	4.3	41.5	61.5
CA454161	1560	3.7	4.8	41.5	61.5
CA374170	1300	3.7	3.7	41.5	70.5
CA544180	2000	3.7	5.4	41.5	80.5
CA3841A3	1600	3.7	3.8	41.5	103.5
CA4841120	2600	3.7	4.8	41.5	120.5
CA6041120	3000	3.7	6.0	41.5	120.5
CA4741C2	2650	3.7	4.7	41.5	122.5
CA414257	1000	3.7	4.1	42.5	57.5
CA454261	1500	3.7	4.6	42.5	61.5
CA6542C2	3700	3.7	6.5	42.5	122.5
CA604355	1500	3.7	6.0	43.5	55.5
CA664364	1900	3.7	6.8	43.5	64.5
CA404380	1500	3.7	4.0	43.5	80.5
CA7043C4	4000	3.7	7.0	43.5	124.0
CA104462	2000	3.7	10.0	44.5	62.5
CA854475	3000	3.7	8.5	44.5	75.5
CA374478	1500	3.7	3.7	44.5	78.5
CA484486	1900	3.7	4.8	44.5	86.5
CA354556	900	3.7	3.5	45.5	56.5
CA624640	1300	3.7	6.2	46.5	40.5
CA524642	1300	3.7	5.4	46.5	42.5
CA524680	2000	3.7	5.2	46.5	80.5
CA604680	2400	3.7	6.0	46.5	80.5
CA7446102	3900	3.7	7.4	46.5	102.5
CA524742	1300	3.7	5.4	47.5	42.5
CA454780	2000	3.7	4.5	47.5	80.5
CA644845	1450	3.7	6.4	48.5	45.5
CA424851	1300	3.7	4.4	48.5	54.5
CA354860	1300	3.7	3.8	48.5	60.5
CA354862	1000	3.7	3.5	48.5	62.5
CA454870	1700	3.7	4.5	48.5	70.5
CA564889	2700	3.7	5.6	48.5	89.5
CA624932	1000	3.7	6.2	49.5	32.5
CA484980	1950	3.7	4.8	49.5	80.5
CA505052	1560	3.7	5.0	50.5	52.5
CA705065	2400	3.7	7.0	50.5	65.5
CA385085	1800	3.7	4.0	50.5	85.5
CA455085	2100	3.7	4.5	50.5	85.5
CA435186	2000	3.7	4.3	51.5	86.5
CA655186	3000	3.7	6.5	51.5	86.5
CA395249	900	3.7	3.9	52.5	49.5
CA555335	1150	3.7	5.7	53.5	35.5
CA295357	800	3.7	2.9	53.5	57.5
CA485383	2100	3.7	4.8	53.5	83.5
CA305585	1300	3.7	3.0	55.5	85.5
CA3555110	2200	3.7	3.6	55.5	110.5
CA505766	2100	3.7	5.0	57.5	66.5
CA3558120	2800	3.7	3.5	58.5	120.5
CA506061	2000	3.7	5.0	60.5	61.5
CA506168	2400	3.7	5.0	61.5	68.5
CA856168	4000	3.7	8.5	61.5	68.5
CA456248	1480	3.7	4.5	62.5	48.5
CA506686	3000	3.7	5.0	66.5	86.5
CA357173	1700	3.7	3.5	71.5	73.5
CA476394	2800	3.7	4.7	63.5	94.5

CA746469	3700	3.7	7.4	64.5	69.5
CA466548	1550	3.7	4.6	65.5	48.5
CA6565C8	5000	3.7	7.3	65.5	128.5
CA556850	1800	3.7	5.5	68.5	50.5
CA6268130	5000	3.7	6.8	70.0	132.0
CA577070	3200	3.7	5.7	70.5	70.5
CA4070107	3300	3.7	4.0	70.5	107.5
CA4270107	3500	3.7	4.2	70.5	107.5
CA387166	2100	3.7	4.1	71.5	66.5
CA357282	2100	3.7	3.5	72.5	82.5
CA287554	1200	3.7	2.8	75.5	54.5
CA397647	1530	3.7	3.9	76.5	47.5
CA447670	2500	3.7	4.4	76.5	70.5
CA387681	2600	3.7	3.8	76.5	81.5
CA588260	3150	3.7	5.8	82.5	60.5